

HyDrone™

Unmanned Surface Vehicle

Seafloor™



TRANSPORTATION AND DEPLOYMENT

HyDrone™ is one person portable, allowing easy access to remote and dangerous areas.

- High-quality marine materials.
- Easily disassembles for transport and shipping.

SEMI-AUTONOMOUS AND REMOTE CONTROL

Controlling the HyDrone™ is easy using a long-range, remote control unit (RCU).

- Up to 1km range.
- Eight hours survey endurance.
- Maneuver easily with powerful differential thrusters.

SOFTWARE COMPATIBILITY

HyDrone™ is compatible with hydrographic data acquisition software such as Hypack, Carlson, EPOCH, Leica, Sokkia, Topcon, and Trimble.

CUSTOMIZATION

- The desired depth sounder can be pre-installed or supplied ready to accept existing equipment from the user's survey pool.
- HyDrone™ can be outfitted with singlebeam, multibeam, sidescan sonar systems and ADCPs.
- Maintain line & fixed heading for ADCP Surveys.
- For professional hydrographic survey requirements, HyDrone™ may be tailored for individual customer specifications. Additional features are available, please contact your Seafloor representative.

The **HyDrone™** is a lightweight, unmanned surface catamaran developed for hydrographic survey applications.

This highly-economical platform provides the same survey results as more expensive remote-controlled systems.



One Person Portable



Differential Thrusters



AutoNav™ Control System



Preplanned route using Mission Planner



Resulting survey data via Mission Planner



HydroLite-TM™ with Trimble GPS and data collector




HyDrone™ ASV with Trimble SPS 585 and TSC3

Seafloor Systems, Incorporated
4415 Commodity Way
Shingle Springs, CA 95682 | USA

HyDrone™

Unmanned Surface Vehicle



Specifications

Typical Survey Speed	2 - 3 kn
Top Speed	6 kn
Hull Length	116 cm / 45.6 in
Hull Width	21cm / 8.2 in
Hull Material	UV Resistant HDPE
Hatches	4 x 7" Twist-Out Watertight Closure
Frame	Aluminum Powder Coated
Hardware	Stainless Steel
Empty Hull Weight & Batteries	9.8 kg / 25 lbs
Battery Endurance	8 Hours at Survey Speed
Payload	15 kg / 35 lbs
Power	2x 14.8 VDC 16 Ah Battery LiPo
Motor	2 x Brushless Thruster
R/C	2.4 GHz
Remote Range	Up to 1km
ECU (Electronic Controller Unit)	2 x 120 amp

Instrumentation Options

HyFi Plus™	AutoNav™ Control System
HydroLite-DFX™	Built-In Telemetry System
HydroLite-TM™	Dual Frequency Echosounder 200/30 KHz
PC Laptop	HydroLite™ Pole Kit
RTKGPS	SonarMite™ MILSpec Echosounder

Seafloor™